



AMF THERMATEX® Mercure



- AMF THERMATEX® Mercure is a white ceiling panel featuring fine perforations, creating a modern, high-quality surface finish
- Good sound absorption (0.60 α_w)
- Good light reflectance (85%)
- Ideal for retail, offices and meeting rooms, installation rooms or production areas





AMF THERMATEX® MERCURE



Edge details	Board	Tegular 24		Tegular 15				
Additional edge details on request	<u> </u>	© 24 24						
Thickness (mm)	15	15		15				
Dimensions (mm) Additional sizes on request	600 x 600 1200 x 600	600 x 600		600 x 600				
System	Exposed demountable - System (C						
Weight	3.6 - 3.8 kg / m²							
Colour	White							
Sound absorption	EN ISO 354 $\alpha_{w} = \textbf{0.60}$ as per EN ISO 11654 Frequency $f(Hz)$ α_{p} NRC = 0.60 as per ASTM C 423	125 0.45	250 0.40	500 1000 0.50 0.70	2000	4000 0.65		
Sound attenuation	EN ISO 10848-2 D _{n,f,w} = 32 dB as per EN ISO 717	EN ISO 10848-2 D _{n,f,w} = 32 dB as per EN ISO 717-1 CAC = 32 dB as per ASTM E 413-10						
Sound reduction	EN ISO 10140-2 R _w = 21 dB as per EN ISO 717-1	ı						
Fire reaction	Euroclass A2-s1, d0 as per EN Class A as per ASTM E 84				M1 (G1, V1, D1, T1) as per 123-FZ			
Light reflectance	85%							
Thermal conductivity	$\lambda = 0.060 \text{ W/mk}$ as per EN 12	$\lambda = 0.060 \text{ W/mk}$ as per EN 12667						
Humidity resistance	95% RH	95% RH						
Indoor air quality	A+ A B C EN 13964	curofins 2002 5000 En Production CG						
Cleanability								
Sustainability	EN ISO 14025 EN ISO 14025 MOSO25 EN ISO 14025	LUBLE WOOL 2000 Annex O						



