

Somplan 350

TECHNICAL DATA	STANDARD	SOMPLAN 350
CLASSIFICATION		
Homogeneous Compact Vinyl Floorcovering	ISO 10581	
Classification	ISO 10874	Classes:
	Commercial	34
	Industrial	43
TECHNICAL CHARACTERISTICS		
Total thickness	ISO 24346	2.0mm
Dimension - Length	ISO 24341	231m
Dimension - Width	ISO 24341	2m
Total weight	ISO 23997	3300g/m ²
Surface treatment		PUR
TECHNICAL PERFORMANCES		
Binder content	ISO 10581	Type II
Dimensional stability	ISO 23999	≤ 0.40% (Rolls)
Curl resistance to heat	ISO 23999	≤ 4.00mm
Reaction to fire	EN 13501-1	B -s1
Residual indentation	ISO 24343-1 measured value	0,43mm
	ISO 10581 requirement	≤ 0.10mm
Castor chair test	ISO 4918 - EN 425	No damage
Thermal resistance	EN ISO 10456	0.04 (m ² ·K)/W
Light fastness	ISO 105 B02	≥ 6
Chemical resistance	ISO 26987	Good resistance
Slip resistance	DIN 51130	R9
	EN 13893	μ ≥ 0.3
Static electrical charge	EN 1815	≤ 2kV
Bacteria resistance	ISO 846-C	Doesn't favour growth
Flexibility	ISO 24344	No crack
ENVIRONMENT		
TVOC 28 days AgBB test	ISO 16000	< 10ug/m ³
Recyclable		100%
Plasticizer		Phthalate-free technology

The above information is subject to modification for the benefit of further improvement.

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Tarkett ROA Sales Offices:

Tarkett Hong Kong Limited
Suite 601B, Empire Centre
68 Mody Road, Tsim Sha Tsui
Kowloon, Hong Kong
Hong Kong SAR
Tel: +852 2511 8716
Email: saleshk@tarkett.com

Tarkett Flooring Singapore Pte.Ltd.
Tel: +65 6346 1585
Email: saleshk@tarkett.com

Tarkett Flooring India Pvt.Ltd.- Bangalore
Tel: +91 80 4130 3793
Email: saleshk@tarkett.com

Tarkett Flooring India Pvt.Ltd. - New Delhi
Tel: +91 11 4352 4073
Email: saleshk@tarkett.com

Tarkett Flooring India Pvt.Ltd. - Mumbai
Tel: +91 22 2648 8750
Email: saleshk@tarkett.com